



SPECIFICATION

Current Rating: 2A AC, DC
 Voltage Rating: 250V AC, DC
 Temperature Range: -25° C ~+85° C
 Contact Resistance: 20 m ohms Max.
 Insulation Resistance: 1,000M ohms Min.
 Withstanding Voltage: 1,500V AC/minute.
 Material: Nylon 66, UL94V-2

Poles	Dimension	
	A	B
2	2.54	5.64
3	5.08	8.16
4	7.62	10.72
5	10.16	13.30
6	12.70	15.78
7	15.24	18.40
8	17.78	20.80
9	20.32	23.50
10	22.86	26.00
11	25.40	28.50
12	27.94	31.00
13	30.48	33.50
14	33.02	36.00
15	35.56	38.50
16	38.10	41.20
17	40.64	43.60
18	43.18	46.32
19	45.72	48.80
20	48.26	51.34

ORDER INFORMATION

H2510 —

02-20 P: Non Distribution Y: W/Locking Rib W: White Fill It With "0" Fill It With "0" Fill It With "0"

			UNIT		SCALE	PART NAME	
			MM		2:1	MX2.54mm HOUSING	
			INCH				
DRAWING.		APPROVED	APPD.	CKD.	TOLERANCE	PART NO.	REV.
Jane					±0.3		A

制表日: 2002/12/04